

SAFETY DATA SHEET

NEW GHS Hazard Categories

Category 1 = Severe Hazard

Category 2 = Serious Hazard

Category 5 = Minimal Hazard

Category 3 = Moderate Hazard

Category 4 = Slight Hazard

SDS No: 0010

Section 1.	Product and Company Identifica	ation			
Product Name:	Hardwood Collection (adhesive)				
Trade Name:	ne: ResinBond				
Recommended Us	se: Signage, Other				
Restrictions on Us	e: None				
				Medcal: 911	
Manufacture:	Rowmark	In Case of Emergency:	Call:	Poison Control: 800-589-3897	
	5409 Hamlet Drive		Email:		
	Findlay, OH 45840	Information:	Call:	1-877-ROWMARK	
			Email:	techhelp@rowmark.com	

Section 2. Hazard Identification

GHS Classification: Not Classified
GHS Label Elements: Not Applicable

Emergency Overview:

APPEARANCE: Various colors; Characteristic Odor

Potential Health Effects:

EYE: Solid or dust may cause irritation or corneal injury due to mechanical action.

SKIN: Essentially non-irritating to the skin. Mechanical injury only. Under normal processing conditions, material is heated to elecated temperatures; contact with the material may cause thermal burns. No adverse effects anticipated by skin absorption.

INGESTION: Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

INHALATION: Inhalation in concentration above 25 to 30 ppm may cause respritory tract injury or death.

GHS Rating

Health	5
Flammability	4
Instability	5
Other	

HMIS Rating

Health	0
Flammability	1
Physical Hazard	0

0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Other Hazards: Not Applicable

Section 3. Composition / Information on Ingredients

Name CAS # % by Weight

Fo	ormaldehyde	50-00-0		0.1-0.5%	
* 5					
* Remaining compo	First Aid Measu	zardous, and/or present at amo	ounts below reportable limits.		
Inhalation:			the nose, throat and respira	tory tract. Remove to fresh air. If not	
illiaution.	Dust and process vapors may be irritation to the nose, throat and respiratory tract. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Medical attention.				
Eyes:		and process vapors may irritate the eyes. Immediately flush eyes with water for at least 15 minutes. Get			
Skin:	Wash affected areas	s with soap and water. G	iet medical advice if rash or p	ersistent irritation or dermatitis occurs.	
Ingestion:	No adverse health e	ffects expected from ing	gestion.		
Section 5.	Fire-Fighting Me	easures			
Suitable Exting	uishing Methods:		Spray, Foam Carbon Dioxide	, or Foam	
	nguishing Methods:	None known.			
Hazards During		Carbon monoxide, ca	arbon dioxide, original monoi	mer other hydrocarbon oxidation products.	
Protective Equi	ipment:	Wear self-contained	breathing apparatus and pro	tective suit.	
Section 6.	Accidental Relea	ase Measures			
Personal Preca	utions:	See Section 8 - Expos	sure Controls / Personal Prote	ection.	
Environmental	Precautions:	No Special environm	ental precautions required.		
Methods and	Materials for Conta	inment and Cleaning	Up		
Spill / Leak:	Containment	of this material should r	not be necessary. Sweep up	or gather material and place in appropriate	
If Molten:	Allow materia	al to cool and place into	an appropriate marked conta	ainer for disposal.	
Section 7.	Handling and St	orage			
Section 7. Handling:	Keep away fro necessary for	om heat, flame and stro safe handling of produc	t. Workers should be protect	usekeeping and controlling dusts are led from the possibility of contact with molte levated temperatures for extended periods	
	Keep away fro necessary for resin during fo time may aut	om heat, flame and stro safe handling of produc abrication. Large masses o-ignite.	t. Workers should be protect s of molten polymer held at e	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods	
	Keep away fro necessary for resin during fo time may aut	om heat, flame and stro safe handling of produc abrication. Large masses o-ignite. om heat, sparks, and flar	t. Workers should be protect s of molten polymer held at e	usekeeping and controlling dusts are led from the possibility of contact with molte	
Handling: Storage:	Keep away fro necessary for resin during fo time may aut Keep away fro from sunlight	om heat, flame and stro safe handling of produc abrication. Large masses o-ignite. om heat, sparks, and flan	et. Workers should be protect s of molten polymer held at e me. Store horizontally in coo	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods	
Handling: Storage: Section 8.	Keep away from necessary for resin during from sunlight	om heat, flame and stro safe handling of produc abrication. Large masses o-ignite. om heat, sparks, and flar	et. Workers should be protect s of molten polymer held at e me. Store horizontally in coo	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods	
Handling: Storage: Section 8. Exposure Lim	Keep away from necessary for resin during from sunlight Exposure Controlits:	om heat, flame and stro safe handling of produc abrication. Large masses o-ignite. om heat, sparks, and flan 	et. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods	
Handling: Storage: Section 8. Exposure Lim 1) Effects of Acc	Keep away from necessary for resin during for time may auto Keep away from sunlight Exposure Controlits: ute Exposure:	om heat, flame and stro safe handling of produc abrication. Large masses o-ignite. om heat, sparks, and flam beland Personal Production	et. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods	
Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chi	Keep away from necessary for resin during from sunlight Exposure Controlits:	om heat, flame and stro safe handling of produc abrication. Large masses o-ignite. om heat, sparks, and flan 	et. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods	
Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chi	Keep away from necessary for resin during from sunlight Exposure Controlits: ute Exposure: ronic Over Exposure:	om heat, flame and stro safe handling of product abrication. Large masses o-ignite. om heat, sparks, and flame bl and Personal Pro See section 11, Toxic See section 11, Toxic	tt. Workers should be protect to of molten polymer held at each me. Store horizontally in coolected tection tection ological Information ological Information	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods of the place in original container and protect	
Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chi 3) OSHA Permis	Keep away from necessary for resin during from may aut Keep away from sunlight Exposure Controlits: Let Exposure: Loronic Over Exposure: Loronic Over Exposure Limits:	om heat, flame and strops af handling of product abrication. Large masses orignite. om heat, sparks, and flame and Personal Profuse See section 11, Toxicon See section 11, Toxicon Chemical Formaldehyde	tt. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection ological Information ological Information OSHA PEL 0.75 ppm TWA 2 ppm STEL	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods of a little process of the contact with moltest periods of the contact p	
Handling: Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chi 3) OSHA Permis	Keep away from necessary for resin during for time may aut Keep away from sunlight Exposure Controlits: ute Exposure: ronic Over Exposure: ssible Exposure Limits:	om heat, flame and strops safe handling of product abrication. Large masses o-ignite. om heat, sparks, and flame and Personal Prosesses section 11, Toxico See section 11, Toxico Chemical	tt. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection ological Information ological Information OSHA PEL 0.75 ppm TWA 2 ppm STEL	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods of a little process of the contact with moltest periods of the contact p	
Handling: Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chi 3) OSHA Permis	Keep away from necessary for resin during from may aut Keep away from sunlight Exposure Controlits: Tote Exposure: Totic Over Exposure: Totic Exposure Limits: Totential: Controls:	om heat, flame and strops as fe handling of product abrication. Large masses orignite. om heat, sparks, and flame and Personal Product See section 11, Toxic Chemical Formaldehyde See section 11, Toxic Chemical Formaldehyde	tt. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection ological Information ological Information OSHA PEL 0.75 ppm TWA 2 ppm STEL	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods of a light of the protect of	
Handling: Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chi 3) OSHA Permis	Keep away from necessary for resin during from may auto Keep away from sunlight Exposure Controlits: Tote Exposure: Tote Exposure Limits: Totential: Controls: Use recommended services and services are services and services are services and services are services and services are services are services and services are servic	om heat, flame and strops af a handling of product abrication. Large masses orignite. om heat, sparks, and flame and Personal Product See section 11, Toxic Chemical Formaldehyde See section 11, Toxic Chemical Formaldehyde	tt. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection ological Information ological Information OSHA PEL 0.75 ppm TWA 2 ppm STEL ological Information	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods of a light of the protect of	
Handling: Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chi 3) OSHA Permis	Keep away from necessary for resin during for time may aut. Keep away from sunlight Exposure Controlits: ute Exposure: ronic Over Exposure: ssible Exposure Limits: Cotential: Controls: Use recommended states	om heat, flame and strops afe handling of product abrication. Large masses orignite. om heat, sparks, and flame and Personal Product and Personal Product See section 11, Toxic Chemical Formaldehyde See section 11, Toxic chemical Formaldehyde	tt. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection cological Information cological Information OSHA PEL 0.75 ppm TWA 2 ppm STEL cological Information o minimize unnecessary experiorage and ordinary handling.	usekeeping and controlling dusts are sed from the possibility of contact with molte elevated temperatures for extended periods of the protect	
Handling: Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chi 3) OSHA Permis 4) Carcinogen P Engineering C	Keep away from necessary for resin during for time may aut Keep away from sunlight Exposure Controlits: ute Exposure: ronic Over Exposure: ssible Exposure Limits: Controls: Use recommended some recommended	om heat, flame and strops afe handling of product abrication. Large masses orignite. om heat, sparks, and flame and Personal Product and Personal Product See section 11, Toxic Chemical Formaldehyde See section 11, Toxic chemical Formaldehyde	tt. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection ological Information ological Information OSHA PEL 0.75 ppm TWA 2 ppm STEL ological Information	usekeeping and controlling dusts are sed from the possibility of contact with molte elevated temperatures for extended periods of the protect	
Handling: Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chi 3) OSHA Permis 4) Carcinogen P Engineering C	Keep away from necessary for resin during for time may aut. Keep away from sunlight Exposure Controlits: Lute Exposure: Loronic Over Exposure: Lissible Exposure Limits: Controls: Use recommended so General room ventil Use local exhaust at tective Equipment:	om heat, flame and stromage response safe handling of product abrication. Large masses orignite. om heat, sparks, and flame and Personal Product See section 11, Toxical Formaldehyde See section 11, Toxical See section 11, Toxical Formaldehyde See section 11, Toxical See section 11, Toxical Formaldehyde	tt. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection cological Information cological Information OSHA PEL 0.75 ppm TWA 2 ppm STEL cological Information o minimize unnecessary experiorage and ordinary handling.	usekeeping and controlling dusts are led from the possibility of contact with molte elevated temperatures for extended periods of a light of the protect of	
Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chi 3) OSHA Permis 4) Carcinogen P	Keep away from necessary for resin during from sunlight Exposure Controlits: Lete Exposure: Loronic Over Exposure	om heat, flame and strops afe handling of product abrication. Large masses orignite. om heat, sparks, and flame and Personal Product and Personal Product See section 11, Toxic See section 11, Toxic Chemical Formaldehyde See section 11, Toxic safe handling practices to ation is adequate for stoppoints of fume generation with side shields or chemical safe safe handling practices to ation is adequate for stoppoints of fume generation with side shields or chemical safe handling practices to a safe handlin	tt. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection ological Information ological Information OSHA PEL 0.75 ppm TWA 2 ppm STEL ological Information o minimize unnecessary exporage and ordinary handling. on or if dusty conditions preventical goggles to prevent eye	usekeeping and controlling dusts are sed from the possibility of contact with molte selevated temperatures for extended periods of the protect of the protec	
Storage: Section 8. Exposure Lim 1) Effects of Act 2) Effects of Chr 3) OSHA Permis 4) Carcinogen P Engineering C	Keep away from necessary for resin during for time may aut Keep away from sunlight Exposure Controlits: Lete Exposure: Lonic Over	om heat, flame and strops af handling of product abrication. Large masses orignite. om heat, sparks, and flame and Personal Product and Personal Product See section 11, Toxic See section 11, Toxic Chemical Formaldehyde See section 11, Toxic safe handling practices to ation is adequate for stopoints of fume generation with side shields or chemical sacilities readily available are stopoints.	tt. Workers should be protect s of molten polymer held at e me. Store horizontally in coo tection ological Information ological Information OSHA PEL 0.75 ppm TWA 2 ppm STEL ological Information o minimize unnecessary exporage and ordinary handling, on or if dusty conditions prev	usekeeping and controlling dusts are sed from the possibility of contact with molte selevated temperatures for extended periods of the protect of the protec	

Appearance: Various colors,	Various color	Vapor Pressure:	Not applicable
Odor:	Characteristic Odor	Vapor Density:	Heavier than Ether
pH:	Not applicable	Relative Density:	<1
Melting Point / Freezing Point:	Not applicable	Solubility (ies):	Insoluble in water
Boiling Point:	208°-210°F	Partition Coefficient (N-Octanol/Water):	Not applicable
Flash Point:	Not Applicable	Auto-Ignition Temperature:	Variable, typically 400-500°F
Evaporation Rate:	Slower than Ether	Decomposition Temperature:	Not applicable
Flammability (solid, gas):	Dust and solid are	Viscosity:	Not applicable
	flammable		
Upper Explosive Limit:	Not established	Specific Gravity:	<1
Lower Explosive Limit:	40 grams/m3	Percent Volatile:	39-44%

Section 10. Stability Reactivity					
Reactivity:	Stable				
Chemical Stability:	Stable				
Possibility of Hazardous Reactions:	None known				
Conditions to Avoid:	Avoid contact with oxidizing agents. Avoid open flames and tempuratures over 400°F				
Incompatible Materials:	None known				
Hazardous Decomposition Products:	Thermal decomposition can produce irritating and toxic fumes and gases, including carbon monoxide, hydrogen cyanide, aldehydes, organic acids and polynuclear aromatic compounds.				

Combustion Products:

Section 11.	Toxicological Information			
Irritation Effects				
	Eye Irritation:	Solid particles may cause transient irritation from mechanical abrasion.		
	Skin Irritation:	Not expected to cause skin irritation. Molten material may cause thermal burns.		
	Inhalation:	Not a likely route of exposure. Process fumes may cause irritation.		
	Ingestion:	May cause a choking hazard if swallowed.		

General Effects of Exposure

Accute Effects of Exposure: Gases and fumes evolved during thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract and cause nausea, drowsiness and headache.

Chronic (non-cancer) Effects of Exposure: Not expected to cause any adverse chronic health effects.

Carcinogenicity:

Formaldehyde is listed by the International Agency for Research on Cancer as a probable human carcinogen. The National Toxicology Program includes formaldehyde in the Annual Report on Carcinogens. Formaldehyde is regulated by OSHA as a potential cancer agent.

Section 12. Ecological Info	ormation
Eco-toxicity:	No relevant studies identified.
Persistence and Degradability:	No relevant studies identified.
Bio-accumulate Potential:	No relevant studies identified.
Mobility in Soil:	No relevant studies identified.
	No relevant studies identified.
Other Adverse Effects:	

Section 13. Disposal Considerations

Disposal Methods

Product Recommendation:

- 1. Recycle (Reprocess) if product has not been contaminated so as to make it unsuitable for its intended use.
- 2. Disposal through controlled incineration or authorized waste dump in accordance with Local, State or Federal Regulations.

Uncleaned Packaging Recommendation:

1. Disposal must be done in accordance with Local, State, or Federal Regulation.

Section 14. Transportation	n Information			
UN Number:	Not Relevant			
UN Proper Shipping Name:	Not Relevant			
Transportation Hazard Class(es)				
DOT:	Not Regulated/classified			
TDG:	Not Regulated/classified			
ADR / RID:	Not Regulated/classified			
IMDG:	Not Regulated/classified			
ICAO/IATA	Not Regulated/classified			
Packing Group:	Not Applicable			
Environmental Hazards:	Not Relevant			
Transportation in Bulk (According to Annex II of MARPOL 73/78 and IBC Code): Not Relevant				
Special Precautions for User:	No special precautions			

Section 15. Regulatory Information

(Not meant to be all-inclusive - selected regulations represented)

NOTICE: The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations. See other sections for health and safety information.

US EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents If discarded in purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste (40 CFR 261.20-24).

OSHA HazCom:	This Material is not Hazardous b OSHA Hazardous Communication Standard 29 CFR 1910.1200			
SARA 313:				
Immediate Hazard: NO		Fire Hazard: NO		Reactivity Hazard: NO
Delayed Hazard: NO		Pressure Hazard: NO		

Section 16. Other Information

No Additional Information

NOTICE: The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In additional, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Revision Date: March 7, 2017